

BP-272C

Thermal Printer



Applications



Shopping



Mart



Restaurant



Hospital



Logistics



Ticketing

www.bopuson.com

BP-272C Thermal Printer



Specifications		
Printer Characteristics	Printer Name	BP-272C
	Printing Method	Direct Thermal
	Resolution	203dpi
	Maximum Printing Speed	250mm/s
	Maximum Printing Width	72mm
	Automatic Cutter	Half Cut(1.5 million cuts)
	Printing Density	576 dot/line or 384 dot /line
	Voice/Command Set	ESC/POS/OPOS
Memory	RAM	2MB
	Flash Memory	2MB (Usb Version); 4MB (Bluetooth Version)
Print Head	Print Head Life	150km
Media Characteristics	Loading Method	Easy Paper Loading Structure/Automatic Feeding
	Paper Type	Label Paper, Continuous Paper, Black Label Paper, Fold Paper
	Width	80mm
	Media Thickness	0.06mm-0.18mm
Operating Parameters	Operating Temperature/Humidity	Temperature: 0°C-45°C Humidity: 20%-90%
	Storage Temperature/Humidity	Temperature: -10°C-60°C Humidity: 10%-90% (Excluding Paper Rolls)
Electrical Specifications	Adapter	DC 24V 2.5A
	Agency Certification Standards	3C Certification
Physical Parameters	Dimension(L*W*H)	194*138*135mm
	Weight	1.13kg
Communication Interfaces and Functions	System Support Platform	WIN2003/WINXP/WIN7/WIN8/WIN10/LINUX/Mac
	Standard Configuration	USB+Lan(Optional: USB/USB+Serial+Lan/USB+Bluetooth/USB+WiFi)
Fonts/Graphics/Symbols	Support Language	Support Most Languages, Other Languages Need To Be Customized
	Character Size	ASCII Font a: 12×24 ASCII Font b: 9×17 Chinese Characters: 24×24
	Extended Character Table	Cp437, Cp850, Cp852, Cp860, Cp863, Cp865, Cp866, Wpc1250, Wpc1251, Wpc1252, Wpc1253, Wpc1254
Barcode Types	1D	UPCA/UPCE/EAN13/EAN8/CODE39/I25/CodeBar/CODE128/CODE93/CODE11/MSI
	2D	QRCODE、PDF417 (Optional)
Certification Specifications	Agency Certification Standards	CCC, CE, ROHS, CB